



1 2 3

系列	代码
NP1	NP1
NPX	NPX
NPH	NPH
NPT	NPT
NPL	NPL
NPG	NPG
NPM	NPM
NPS	NPS
VP1	VP1
VP4	VP4
VPX	VPX
VPH	VPH
VPT	VPT
VPL	VPL
VPG	VPG
VPM	VPM
VPS	VPS
NGY	NGY
NHT	NHT
VHX	VHX
VGY	VGY
VHT	VHT
VHM	VHM
VHU	VHU
VHR	VHR

4 5 6 7

产品直径	代码	产品高度	代码
3.55	W	3.55	035
4	A	3.95	039
4.5	G	4.5	045
5	B	5	050
5.5	H	5.4	054
6.3	C	5.8	058
8	D	6.5	065
10	E	7	070
12.5	L	7.7	077
16	I	8	080
18	J	8.5	085
20	N	9	090
22	K	9.5	095
25	M	10	100
30	P	10.5	105
		11	110
		11.5	115
		12	120
		12.5	125
		13	130
		13.5	135
		14	140
		14.5	145
		15	150
		16	160
		16.5	165
		17	170
		18	180
		19	190
		20	200
		25	250
		31.5	315
		35.5	355

8 9

额定电压(V)	代码
2	0D
2.5	0E
4	0G
6.3	0J
6.8	0A
7.5	0L
10	1A
12	1B
14	1Q
16	1C
18	1M
20	1D
25	1E
35	1V
40	1G
45	1W
50	1H
55	1I
63	1J
80	1K
90	1F
100	2A
110	2R
125	2B
140	2Q
160	2C
180	2M
200	2D
250	2E
400	2G

10 11 12

静电容量(μF)	代码
1.0	1R0
1.5	1R5
2.2	2R2
2.7	2R7
3.3	3R3
4.7	4R7
5.6	5R6
6.8	6R8
8.2	8R2
10	100
12	120
15	150
18	180
22	220
27	270
33	330
39	390
47	470
56	560
68	680
82	820
100	101
120	121
150	151
180	181
220	221
270	271
330	331
390	391
470	471
560	561
680	681
820	821
1000	102
1200	122
1500	152
1800	182
2000	202
2200	222
2500	252
2700	272
3300	332
3900	392
4700	472
5600	562
6800	682
8200	822
10000	103

13

容量范围	代码
±20%	M
±10%	K

14

附属码(引脚成型)	
A	切直脚A图
B	切脚成型B图
C	切脚成型C图
D	切脚成型D图
E	切脚成型E图
Q	切脚折弯90° F图A型(右)
P	切脚折弯90° F图B型(左)
X	切脚成型G图
G	切脚双折弯90° H图A型(右)
R	切脚双折弯90° H图B型(左)
K	编带A图
L	编带B图
V	SMD
J	固态引线型

15 16

附属码(外观)	
JG	胶管
TM	涂膜丝印
CG	车规
KZ	抗震品
MR	品红色涂膜丝印
JP	军规